

Продаются новые коммутаторы Cisco



AvizInfo.com.ua

Київ, Україна

Продаются новые коммутаторы Cisco

WS-C3750-24PS-S Catalyst 3750 24 10/100 PoE + 2 SFP + IPB Image - 6шт

General

Device Type Switch - stackable

Enclosure Type Rack-mountable - 1U

Width 17.5 in

Depth 11.8 in

Height 1.7 in

Weight 11.2 lbs

Memory

RAM 128 MB

Flash Memory 16 MB flash

Networking

Ports Qty 24 x Ethernet 10Base-T, Ethernet 100Base-TX

Max Units In A Stack 9

Data Transfer Rate 100 Mbps

Data Link Protocol Ethernet, Fast Ethernet

Routing Protocol RIP-1, RIP-2, EIGRP, static IP routing, RIPng

Remote Management Protocol SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, SSH

Connectivity Technology Wired

Communication Mode Half-duplex, full-duplex

Switching Protocol Ethernet

MAC Address Table Size 12K entries

Status Indicators Port status, link activity, port transmission speed, port duplex mode, status

Features Flow control, full duplex capability, layer 3 switching, auto-sensing per device, IP-routing, DHCP support, power over Ethernet (PoE), auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, traffic shaping, stackable, IPv6 support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS)

Compliant Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s

Expansion / Connectivity

AvizInfo.com.ua

1/2

Expansion Slots Total (Free) 2 (2) x SFP (mini-GBIC)
 Interfaces 24 x network / power - Ethernet 10Base-T/100Base-TX - RJ-45 female

1 x management - console - RJ-45 female
Network stack device
Miscellaneous

MTBF 209, 170 hour(s)

Authentication Method Kerberos, Secure Shell (SSH), RADIUS, TACACS+

Compliant Standards CE, FCC Class A certified, TUV GS, BSMI CNS 13438 Class A, CISPR 24, cUL, EN 60950, EN55022, NOM, VCCI Class A ITE, IEC 60950, EN55024, UL 60950 Third Edition, CISPR 22, CSA 22.2 No. 60950, CB, FCC Part 15, MIC, AS/NZS 3548

Power

Power Over Ethernet (PoE) Yes

Power Device Power supply - internal

Voltage Required AC 120/230 V (50/60 Hz)

Power Consumption Operational 495 Watt

Features Redundant Power System (RPS) connector

Software / System Requirements

Software Included Cisco IOS IP Base

Manufacturer Warranty

Service & Support Limited lifetime warranty

Service & Support Details Limited warranty - lifetime

Environmental Parameters

Min Operating Temperature 32 °F

Max Operating Temperature 113 °F

Humidity Range Operating 10 - 85%

Max Altitude Operating 9840 ft

Price: **1 700 \$**

Тип оголошення:
Продам, продаж, продаю

Торг: доречний

Мащук Максим

+380633356811